

Nord Technology

Distributor of SolidRun hardware in Northern Europe

NORD TECHNOLOGY CONTACT INFORMATION

World Trade Center
Borupvang 3,
2750 Ballerup,
Denmark

 **Tel.:** +45 70 27 04 15
 **Email:** sales@nord-t.eu
 **Website:** www.nordtechnology.dk

Bedrock R7000 Basic



SolidRun Bedrock R7000 Basic Specifications

Feature	Specification	Notes
CPU	AMD Ryzen™ 7040 Series 8C/16T Zen4 4nm Up to 5.1 GHz Up to 54W	
GPU	AMD Radeon™ 780M	Up to 12 CU @ 2700 MHz
RAM	Dual channel DDR5 up to 64 GB ECC / non-ECC	2x SODIMM (2x32 bit each) RAM is conduction cooled
Display	1x HDMI 2.1 1x Display Port 2.1 2x mini-DisplayPort 2.1	Max resolution / refresh rate: 7680x4320 @ 60Hz 3840x2160 @ 240Hz
Main storage	NVMe PCIe Gen4 x 4	M.2 key-M 2280 Optional power-loss-protection NVMe is conduction cooled
Extra storage	2x NVMe PCIe Gen4 x 4	2x M.2 key-M 2280 NVMe devices are conduction cooled
LAN	2x 2.5 GbE (Intel I226)	2x RJ45
WLAN	WiFi 6E (Intel AX210) BT 5.3	2x RP-SMA antennas Optional and upgradable (M.2 key-E 2230)
Modem	4G / 5G (Quectel)	2x SMA antennas Optional and upgradable (M.2 key-B 3042 / 3052)
USB	1x USB 3.2 gen 2 10 Gb/s 3x USB 3.2 gen 2 5 Gb/s	Connectors: 4x USB type-A
Console	Serial over USB	mini-USB connector
BIOS	AMI Aptio V	Dual SPI FLASH for redundancy Console redirection
Operating systems	Windows 10/11/IoT, Linux	Other x86 operating systems supported
Power	DC 12V-60V	Phoenix terminal Other DC connectors available
Temperature range	Up to -40°C to 85°C	Also available in commercial temperature range
Enclosure	All aluminum enclosure, fanless cooling	
Dimensions	30W model: 45 mm (W) x 160 mm (H) x 130 mm (D) - 0.9 liter 60W model: 73 mm (W) x 160 mm (H) x 130 mm (D) - 1.5 liter Tile model: 29 mm (W) x 160 mm (H) x 130 mm (D) - 0.6 liter	
Mounting	DIN-rail, wall, table top	

23-Jul-2023