

Nord Technology

Reseller of Taicenn hardware in Denmark

NORD TECHNOLOGY CONTACT INFORMATION

World Trade Center
Borupvang 3,
2750 Ballerup,
Denmark

-  **Tel.:** +45 70 27 04 15
-  **Email:** sales@nord-t.eu
-  **Website:** www.nordtechnology.dk

Control Cabinet Industrial PCs TBOX-6xx5





Control Cabinet Industrial PCs TBOX-6xx5

- Rugged & Slim design, fanless design;
- Intel 12th Gen. Alder Lake -N/-U processors;
- Single DDR4 memory, up to 32GB, 1* M.2 2280 NVMe storage;
- DC terminal 12V input, optional DC 24V input;
- 2 GbE, optional with Wi-Fi/BT wireless function;
- 6 USB3.0, 1 HDMI, 1 DP, Audio;
- 2 M.2 fast-speed expansion slots;
- Cabinet mount, optional Din-Rail mount;
- Industrial operating -20 ~ +60 °C temp. range.

TBOX-6N15 Specs

System	BIOS	SPI AMI EEI BIOS
	CPU	Intel 12 th Gen. Alder Lake-N series N97 processor, up to 3.6Ghz, 4E-Core
	CPU Ghz	Up to 3.6Ghz, 4E-Core
	TDP	12W
	Graphic	Intel UHD Graphics (Up to 24EUs, 1.2Ghz)
	TPM	Intel PTT TMP2.0
	Memory	SO-DIMM, DDR4-2666/2933/3200 Mhz, Single slot, Max. up to 16GB
	Storage	1* M.2 2280 M-Key slot (PCIe x1 & SATA) SSD
	Network	1* Intel I226V, 1* Intel I210AT, Optional support Wi-Fi/BT & Wi-Fi 6 wireless
	Expansion	1* M.2 3042/3052 B-key slot, 1* M.2 E-key slot (Wi-Fi/BT)
	Watchdog	0 ~ 256 seconds programmable
	Operating system	Win10/Win11 64-bit; Linux
IO interface	Serial port	N/A
	Ethernet	2* RJ45, 10/100/1000 Mbps
	USB	4* USB3.0, 2* USB2.0,
	Display	1* HDMI (Max. support 4096 *2160 @30Hz), 1* DP++ (Max. 4096*2160 @60Hz)
	Audio	1* Mic-in/Line-out (2-in-1, 3.5mm Jack)
	Power input	1* 2 pin, DC terminal
Structure	Box structure and surface	Aluminum alloy, anodizing and anti-scratch treatment
	Color	Black
	Mount method	Cabinet mount, Din-Rail mount (optional)
	Cooling system	Finned aluminum heatsinks
	Indicator & Button	Power switch, Power LED, HDD LED
	Dimension	150.00mm * 114.00mm * 47.00 mm (194.00mm with mount rack)
	Net weight	About 1.0 KG
Power & Environmental	Operating temp.	-20 ~ + 60 (°C)
	Storage temp.	-40 ~ + 80 (°C)
	Humidity	10 ~ 95% @ 10C (No condensation)
	Vibration	50 ~ 500 Hz, 1.5G, 0.15mm peak to peak
	Shock	10G/Peak (11 ms)
	Power input	DC 12V (optional wide DC 9 ~36V range)
	Power consumption	About 25W
	Certificate	CE/FCC/ROHS

TBOX-6Dx5 Specs

System	BIOS	SPI AMI EEI BIOS
	CPU	Intel 12 th Gen. Alder Lake-U Core i5-1235U processor, 2P/8E-Core
	CPU Ghz	P-core Up to 4.40Ghz; E-core up to 3.30Ghz
	TDP	15W
	Graphic	Intel Iris Xe Graphics eligible (Up to 80 EUs, 1.2Ghz)
	TPM	Intel PTT TMP2.0
	Memory	SO-DIMM, DDR4-2666/2933/3200 Mhz, Single slot, Max. up to 32GB
	Storage	1* M.2 M-Key (PCIe x4 / SATA, Default PCIe 4x, Gen. IV NVMe, 2280) SSD slot
	Network	1* Intel I219AT, 1* Intel I226V, Optional support Wi-Fi/BT wireless
	Expansion	1* M.2 3042/3052 B-key slot, 1* M.2 E-key slot (Wi-Fi/BT)
	Watchdog	0 ~ 256 seconds programmable
	Operating system	Win10/Win11; Linux Kernal 5.17 or later
	IO interface	Serial port
Ethernet		2* RJ45, 10/100/1000 Mbps
USB		6* USB3.0
Display		1* HDMI (Max. support 2048 *1080 @30Hz), 1* DP++ (Max. 4096*2304 @60Hz)
Audio		1* Mic-in/Line-out (2-in-1, 3.5mm Jack)
Power input		1* 2 pin, DC terminal
Structure	Box structure and surface	Aluminum alloy, anodizing and anti-scratch treatment
	Color	Black
	Mount method	Cabinet mount, Din-Rail mount (Optional)
	Cooling system	Finned aluminum heatsinks
	Indicator & Button	Power switch, Power LED, HDD LED
	Dimension	150.00mm * 114.00mm * 47.00 mm (194.00mm with mount rack)
	Net weight	About 1.0 KG
Power & Environmental	Operating temp.	-20 ~ + 60 (°C)
	Storage temp.	-40 ~ + 80 (°C)
	Humidity	10 ~ 95% @ 10C (No condensation)
	Vibration	50 ~ 500 Hz, 1.5G, 0.15mm peak to peak
	Shock	10G/Peak (11 ms)
	Power input	DC 12V (Optional wide DC 9~36V)
	Power consumption	About 25W
	Certificate	CE/FCC/ROHS